

BRCS045N08SHBD

Rev.A Dec.-2023

描述 / Descriptions

TO-263 塑封封装 N 沟道场效应管。
N-CHANNEL MOSFET in a TO-263 Plastic Package.


特征 / Features

$V_{DS}=80V$ $I_D=155A$
 $R_{DS(on)}@10V \leq 4.5m\Omega$ (Type.3.5m Ω)
 $R_{DS(on)}@6V \leq 9.0m\Omega$ (Type.4.7m Ω)
 无卤产品。HF Product.


用途 / Applications

升压转换器和用于消费电子、电信和工业的同步整流器，电源和 LED 背光。
 Boost converters and synchronous rectifiers for consumer, telecom, industrial power supplies and LED backlighting.

内部等效电路 / Equivalent Circuit



引脚排列 / Pinning



PIN 1 : G PIN 2、4 : D PIN 3 : S

印章代码 / Marking

见印章说明。
See Marking Instructions.

极限参数 / Absolute Maximum Ratings(Ta=25°C)

参数 Parameter		符号 Symbol	数值 Rating	单位 Unit
Drain-Source Voltage		V _{DSS}	80	V
Drain Current		I _D (Tc=25°C)	155	A
Pulsed Drain Current		I _{DM}	322	A
Gate-Source Voltage		V _{GS}	±20	V
Single Pulsed Avalanche Energy(L=0.5mH)		E _{AS}	986	mJ
Avalanche Current		I _{AS}	43	A
Total Power Dissipation		P _D (Tc=25°C)	200	W
Junction and Storage Temperature Range		T _J , T _{STG}	-55 to 150	°C
Thermal Resistance-Junction to Ambient	Steady-State	R _{θJA}	62.5	°C/W
Thermal Resistance-Junction to Case	Steady-State	R _{θJC}	0.63	

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions		最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V	I _D =250μA	80	92.5		V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =80V	V _{GS} =0V			1	μA
Gate-Body Leakage Current Forward	I _{GSS}	V _{GS} =±20V	V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS}	I _D =250μA	2	3	4	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V	I _D =20A		3.5	4.5	mΩ
	R _{DS(on)}	V _{GS} =6V	I _D =10A		4.7	9	
Forward On Voltage	V _{SD}	V _{GS} =0V	I _S =1A			1.4	V
Gate resistance	R _g	f=1MHz			1		Ω
Input Capacitance	C _{iss}	V _{DS} =25V f=1MHz V _{GS} =0V			4240		pF
Output Capacitance	C _{oss}				2550		
Reverse Transfer Capacitance	C _{rss}				150		
Total Gate Charge	Q _g	V _{GS} =10V, I _D =20A V _{DS} =40V,			73		nC
Gate Source Charge	Q _{gs}				19.2		
Gate Drain Charge	Q _{gd}				12		

电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=40V$ $R_L=2\Omega$ $R_{GEN}=3\Omega$		19		ns
Turn-On Rise Time	t_r			12.5		
Turn-Off Delay Time	$t_{d(off)}$			40		
Turn-Off Fall Time	t_f			8		

电参数曲线图 / Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

电参数曲线图 / Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10: Normalized Maximum Transient Thermal Impedance

外形尺寸图 / Package Dimensions




单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	4.30	4.70	E	9.00	9.40
B	1.00	1.40	e1	2.34	2.74
b	0.70	0.90	e2	4.88	5.28
b1	1.15	1.35	L1	15.00	16.00
b2	0.40	0.60	L2	2.24	2.84
C	1.20	1.40	L3	1.20	1.60
D	9.80	10.20			

TO-263

印章说明 / Marking Instructions



说明：

BR： 为公司代码

045N08SH： 为型号代码

****： 为生产批号代码，随生产批号变化


Note:

BR: Company Code

045N08SH: Product Type Code

****: Lot No. Code, code change with Lot No

回流焊温度曲线图(无铅) / Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 1、预热温度 150~180°C，时间 60~90sec;
- 2、峰值温度 245±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2~10°C/sec.

Note:

- 1.Preheating:150~180°C, Time:60~90sec.
- 2.Peak Temp.:245±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：260±5°C

时间：10±1 sec.

Temp.:260±5°C

Time:10±1 sec

包装规格 / Packaging SPEC.

卷盘包装 / REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-263	800	1	800	6	4,800	13" ×24	360×360×50	380×335×366

套管包装 / TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-263	50	20	1,000	5	5,000	532×33×7.0	555×164×50	575×290×180

使用说明 / Notices